

# GLASS TEMPERING OVEN



MYIU\_9-

## Roller chain conveyor

	Original Bearing	EDT Bearing
Bearing	Graphite bearing in cast iron housing (bearing runs directly on the shaft, no shaft protection)	<b>MYIUC9-1, All-Round® insert with extended-length locking sleeve for shaft expansion can be installed into existing metal housing</b>
Failure	Bearing wears shaft which then needs replacement	<b>Routine bearing wear; replace insert and re-use locking sleeve.</b>
Length of Service	3 months	<b>18 months</b>
Maintenance Required	Replace shaft damaged by bearing	<b>Reduced bearing replacements. Eliminate shaft damage.</b>
Features & Benefits	Low initial cost	<b>Longer life Reduced maintenance time Lower lifecycle cost</b>



## BLEACH FILLER



NA6AC7-1



NA6GC7-1

## Tabletop chain and Modular plastic belts

	Original Bearing	EDT Bearing
Bearing	Standard steel bearing insert in cast iron housing	<b>NA6AC7-1, NA Poly-Round® with locking sleeve in stainless or polymer housing</b>
Failure	Bleach wash and heavy washdown caused bearings to corrode and fail	<b>Holding up against bleach splash and routine washdown insert will wear after approximately a year</b>
Length of Service	3-4 months	<b>1+ year</b>
Maintenance Required	Frequent lubrication and frequent replacement	<b>None</b>
Features & Benefits	Low cost	<b>No rust, no maintenance, long life, less down-time to catastrophic failure. Lower cost of ownership</b>